

SU1 SLD G

SPECIFICATIONS

Nominal Voltage (V)	12V
Capacity at C/100	36.5Ah
Weight	23.4 Lbs. (10.6 kg)
Plate Alloy	Lead Calcium
Posts	Forged terminals & bushings
Container/Cover	Polypropylene
Operating Temperature Range	-76°F (-60°C) – 140°F (60°C)
Charge Voltage @ 68°F (20°C)	
Cycle	2.30 - 2.35 VPC
Float	2.25 - 2.30 VPC
Vent	Self-sealing (2 PSI operation)
Electrolyte	Sulfuric acid thixotropic gel
Resistance	4.0 Milliohms (full charge)
Terminal	T873

Rated non-spillable by ICAO, IATA and DOT
Approved by CEC

Made in the U.S.A by East Penn Manufacturing

Distributed by:


Valve-Regulated, Gelled-Electrolyte Battery



DIMENSIONS

Length (mm)	7.75 (197 mm)
Width (mm)	5.13 (130 mm)
Height (mm)	7.25 (184 mm)

Gel Cycle Life vs Depth of Discharge at +25°C (77°F)
Based on BCI 2-hour Capacity



Cycle Chart applies to all MK Gel batteries (except 8G6C2 cycle chart x 2, 8G24/8G27 with a T872M terminal and 8G31DT cycle chart x .67).

MK Battery

1645 South Sinclair Street • Anaheim, California 92806
Toll Free: 800-372-9253 • Fax: 714-937-0818 • E-Mail: sales@mkbattery.com

